PATENT NC 95,884

What is claimed is:

1. A pack to safely carry energetic materials and energetic initiators, comprising: an energetic material section having an opening and closure means to close the opening; an energetic initiator section, comprising:

a second opening;

second closure means to close the second opening;

a fabric comprising at least one layer of a conductive material substantially surrounding the energetic initiator section with a back panel between the energetic material section and the energetic initiator section having at least one layer of blast resistant and fragmentation inhibiting material.

2. The pack of claim 1, wherein the energetic initiator section further comprises: an initiator containment panel, removably attached to the back panel, comprising at least one layer of blast resistant and fragmentation resistant material;

a second fabric comprising at least one layer of blast resistant and fragmentation inhibiting material attached to the initiator containment panel forming a plurality of initiator holder pockets; and,

a third fabric, substantially adjacent to a plurality of bottoms of the plurality of initiator holder pockets and adjacent to an outer edge of the of the pack, comprising at least one layer of blast resistant and fragmentation inhibiting material.

- 3. The pack of claim 2, wherein the plurality of initiator holder pockets further comprise two concentric plastic tubes having an air gap therebetween.
- 4. The pack of claim 3, wherein the initiator containment panel further comprises at least one layer of polycarbonate material which hardens when impacted by a projectile.

PATENT NC 95,884

5. The pack of claim 2, wherein the back panel comprises two layers of a nylon material and two layers of a blast resistant and fragmentation inhibiting material and one layer of conductive material therebetween.

. 1

- 6. The pack of claim 4, wherein the plurality of initiator holder pockets further comprise two layers of a nylon material having two layers of the blast resistant and fragmentation inhibiting material therebetween.
- 7. The pack of claim 2, wherein the third fabric further comprises at least one layer of polycarbonate material which hardens when impacted by a projectile.
- 8. The pack of claim 2, further comprising a plurality of initiator holder pocket tops, removeably attached to the plurality of initiator holder pockets wherein the initiator holder pocket tops keep the initiators within the initiator holder pockets until the initiator holder pocket tops are removed.
- 9. The pack of claim 5, wherein the initiator containment panel comprises two layers of a polycarbonate material which hardens when impacted by a projectile surrounded by four layers of blast resistant and fragmentation inhibiting material surrounded by two layers of nylon.
- 10. The pack of claim 9, wherein the third fabric comprises a layer of blast resistant and fragmentation inhibiting material surrounded by two layers of polycarbonate material which hardens when impacted by a projectile surrounded by four layers of blast resistant and fragmentation inhibiting material surrounded by two layers of nylon.
- 11. The pack of claim 10, wherein the second closure means comprises a zipper covered by a flap of the fabric when the zipper is closed.
- 12. A safe method of transporting primary explosives and initiators, comprising the steps of:

PATENT NC 95,884

providing a pack having a first section and a second section, at least one layer of blast
resistant and fragmentation inhibiting material between the first and second section and at least
one layer of a conductive material surrounding the second section;

placing the primary explosives within the first section; and, placing the initiators within the second section.

- 13. The method of claim 14, wherein the pack further comprises at least one layer of a polycarbonate material which hardens when impacted by a projectile.
- 14. The method of claim 15, wherein the pack further comprises multiple layers of polycarbonate material which hardens when impacted by a projectile, blast resistant and fragmentation inhibiting material, nylon between the first and second sections.